

MODELLO: MAINBOARD ASUS P5LD2-VM I945G SKT-775 V-A-L
MODELLO PRODOTTO: MAINBOARD ASUS P5LD2-VM I945G SKT-775
MODELLO PRODUTTORE: P5LD2-VM-EAYGZ

Informazioni prelevate dal sito internet: ` http:``www.asus.com.tw`

CPU: Socket 775 for Intel Pentium D / Pentium 4 / Celeron
Intel® EM64T / EIST / Hyper-Threading Technology
Chipset: Intel 945G
Intel ICH7
Front Side Bus: 1066/800/533 MHz
Memory: 4 x DIMM, max. 4GB, DDR2 667/533, non-ECC, un-buffered memory
Dual Channel Architecture
Expansion Slots: 1 x PCI-E x16
1 x PCI-E x1
2 x PCI
PCI 2.2
VGA: Intel Graphics Media Accelerator 950
Storage/RAID: Intel ICH7 South Bridge:
1 x UltraDMA 100/66/33
4 x Serial ATA 300/150
ITE IDE controller:
1x UltraDMA 133/100
Audio: Realtek ALC 882, 8-ch High-Definition Audio CODEC
S/PDIF out interface
LAN: Intel Gb LAN
USB: 8 USB2.0 ports
Other ASUS
Special Features: ASUS AI Overclocking
ASUS EZ Flash
ASUS MyLogo2
ASUS C.P.R.
ASUS Q-Fan
ASUS CrashFree BIOS 2
Back Panel I/O Ports: 1 x Parallel
1 x Serial
1 x PS/2 Keyboard
1 x PS/2 Mouse
1 x VGA
1 x Audio I/O
1 x RJ45
4 x USB
Internal
I/O Connectors: 2 x USB connectors supports additional 4 USB ports
CPU / Chassis FAN connectors
24-pin EATX Power connector
4-pin ATX 12V Power connector
Chassis Intrusion connector
S/PDIF out connector
CD audio in
3-pin PWR FAN connector
Front panel High Definition Audio connector
Manageability: WfM 2.0, DMI 2.0, WOL by PME, PXE, RPL, Chassis Intrusion, SM Bus
Support CD: Drivers
ASUS PC Probe II
Anti-Virus Software
ASUS LiveUpdate
Accessories: User`s manual
UltraDMA cable
IDE cable
FDD cable
I/O shield

SATA cables

*All specifications are subject to change without notice.
2005 ASUSTeK Computer Inc. All rights reserved.